




SAI SYSTEMS
committed to perfection

An ISO 9001 : 2008 Certified Company

www.saisysindia.com

Manufacturers of testing & Measuring Instruments
and Accessories for Electronic Instrumentation



1-34/43, Sarvodaya Nagar, Near Aaray Signal, Western Express
Highway, Goregaon (E), Mumbai. 400063. Maharashtra, INDIA
Email : saicomponents@yahoo.com

Tele Phones
022-29277177
022-29277188

Knobs



Knob with Super Grip

PN-1 25mm Super gripped round knob with cap
Choice of colour combinations for bottom, body and cap. Knob covers mounting nut of potentiometer



Base Dia: 25mm
Height: 17mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Mini Winged Knob

PN-10 Double Winged Mini knob with line



Base Dia: 16mm
Height: 15.4mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Round Knob

PN-28/N 28mm Round Knob with line



Base Dia: 28mm
Height: 20mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Miniature Knob Slip-on type


PN-2 20mm Super gripped round knob with cap
Choice of colour combinations for bottom, body and cap. Knob covers mounting nut of potentiometer



Base Dia: 20mm
Height: 14.8mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Mini Winged Knob Snap-in-type

PN-10/P Double Winged Mini knob with line for snap-in 'D' type shafts



Base Dia: 16mm
Height: 15.4mm
Shaft Dia: 4mm D type
Snap-in-type
Available in all Standard Colours

Winged Knob with Cap


PN-33 Four Winged knob with Line marked Cap
Choice of colour combination for Body & Cap



Base Dia: 22.8mm
Height: 20.6mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Miniature Knob Slip-on type

PN-3 10mm Miniature knob with line for 4mm 'D' type plastic or metal shaft



Base Dia: 9.5mm
Height: 12.5mm
Shaft Dia: 4mm D-type
Slip-on-type
Available in all Standard Colours

Dual Knob Assembly

PN-12 40mm Base knob with Top Transparent Dial and Top Knob



Base Dia: 40mm
Height: 31mm
Top Knob Dia: 25mm
Shaft Dia: Base Knob: 6.4mm
Top Knob: 2.1mm
Snap-in-type
Screw fixing
Available in all Standard Colours

Point Marked Collar Knob


PN-35 16mm Pointer knob with Collar



Base Dia: 16mm
Height: 15.3mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Miniature Knob Slip-on type


PN-3/B 10mm Miniature Knob Slip-on-type



Base Dia: 10mm
Height: 13mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Slip-on-type
Available in all Standard Colours

Square Marked Knob

PN-15 20mm Knob Square Marked



Base Dia: 20mm
Height: 15.8mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Slip-on-type Collar Knob

PN-35/P 16mm Slip-on-type Collar knob with 4 different orientations



Base Dia: 16mm
Height: 15.3mm
Shaft Dia: 4mm
For plastics shafts slip-on-type in 4 different orientations
Available in all Standard Colours

Miniature Dual Knob Assembly

PN-4 19mm Mini Dual knob assembly for Dual type potentiometers



Base Dia: 19mm
Height: 24.5mm
Base Shaft Dia: 6.1mm/6.4mm
Top Shaft Dia: 2.1mm
Screw fixing
Available in all Standard Colours

Lined Round Knob

PN-23 21mm Round knob with line



Base Dia: 21mm
Height: 16mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Winged Knob with Line

PN-36 22mm Winged Knob with Line



Base Dia: 22.8mm
Height: 19.3mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Single Winged Round Knob


PN-5 Single Winged Round Knob with Line & Cap



Base Dia: 19.6mm
Height: 14.8mm
Shaft Dia: Base: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Round Knob Slip-in-type

PN-23/P 21mm snap-in-type knob for 6mm D type shaft



Base Dia: 21mm
Height: 16mm
Shaft Dia: 6mm D type
Snap-in-type
Available in all Standard Colours

Point Marked Knob


PN-37 13mm Pointer Knob



Base Dia: 13mm
Height: 15mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Miniature Winged Knob


PN-6 Four Winged miniature knob with line. (For miniature rotary switch appliances)



Base Dia: 19mm
Height: 16.5mm
Shaft Dia: 4mm
Screw fixing
Available in all Standard Colours

Square Marked Knob

PN-24 25mm Round Knob with Square Mark



Base Dia: 25mm
Height: 16.5mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Pointer Knob Slip-on-type

PN-38 13mm Point Marked Slip-on-type knob in four different orientations



Base Dia: 13mm
Height: 15mm
Shaft Dia: 4mm
For plastic shafts slip-on-type in 4 different orientations
Available in all Standard Colours

Single Winged Knob

PN-7 25mm Single Winged knob with line (for high torque applications)



Base Dia: 25mm
Height: 21mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Wide Knob with Lined Cap


PN-27 40mm Knob with lined Cap



Base Dia: 40mm
Height: 14mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Dual Knob Assembly

PN-41 Four Winged Dual Knob Assembly



Base Dia: 22.8mm
Height: 31.5mm
Base Shaft Dia: 6.4mm
Top Shaft Dia: 2.1mm
Screw fixing
Available in all Standard Colours

Knobs



Arrow marked round Knob

PN-42 42mm arrow marked round knob with Curve marked cap & Base For dummy front panel Instruments



Base Dia: 42mm
Height: 22mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Knob with Lined Cap

SK-19/P 19mm Slip-on-type knob with Cap



Base Dia: 19.5mm
Height: 16mm
Shaft Dia: 6.1mm D shaft
Slip-on-type
Available in all Standard Colours

Single Winged Knob with Dial

SK-25/D 25mm Single Winged Knob with 44mm arrow marked dial



Dial Base Dia: 44mm
Height: 20mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Giant Knob

VK-60 60mm Knob Specially designed for Variac Mounted Instruments



Base Dia: 60mm
Height: 16.5mm
Shaft Dia: 6.4mm/8.1mm
Screw fixing
Available in all Standard Colours

Knob with Cap & Dial

SK-19/D 19mm Knob with Cap & 30.6mm Transparent Dial



Knob Dia: 19.5mm
Dial Dia: 30.7mm
Height: 21.2mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Round Knob with Curved Cap

SK-28/R 38mm Round knob with curved Cap



Base Dia: 38mm
Height: 18.5mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Tri-Winged Knob

WK-25 25mm Tri-Winged Knob with Self embossed line & Cap



Base Dia: 25mm
Height: 16.5mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Round Knob with Dial

SK-35 25mm Square marked Round Knob with 35mm marked Dial



Knob Dia: 25mm
Dial Dia: 35mm
Height: 20mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Round Knob with Lined Cap

SK-28/P 38mm Round knob with Lined Plane Cap



Base Dia: 38mm
Height: 19mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Dual Knob Assembly

DK-35 29mm Dual Knob Assembly Specially designed for Dual-dial readings



Height: 22.8mm
Wing Dia: 35mm
Top Dia: 24mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Single Winged Collet Knob

SK-5 20mm Single Winged Collet knob with embossed Line & Cap



Base Dia: 20mm
Height: 15.7mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet type
Available in all Standard Colours

Single Winged Knob with Cap

SK-30 30mm Single Winged knob with Line & Cap



Knob Dia: 30mm
Wing Dia: 34.5mm
Height: 18.5mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Tri-Winged Knob with Cap

WC-25 25mm Tri-Winged Knob embossed with line & Cap



Base Dia: 25mm
Height: 17mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Round Collet Knob

SK-10 19.5mm Collet Knob with self embossed line & Cap



Base Dia: 19.5mm
Height: 15.6mm
Shaft Dia: 6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Single Winged Knob with Dial

SK-30/D 30mm Single Wing Lined knob with Cap, & 50mm arrow marked Dial



Knob Dia: 30mm
Dial Base Dia: 50mm
Height: 23mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Tri-Winged Knob

TWK-20 25mm Tri-Winged with Self Marked Knob



Base Dia: 20mm
Height: 16.6mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Single Winged Collet Knob

SK-15 15mm Single Winged Collet knob



Knob Dia: 15mm
Wing Dia: 17mm
Height: 17.5mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Round Knob with Marked Dial

SK-45 Triple Winged 25mm knob with embossed line & 44mm arrow marked dial



Knob Dia: 25mm
Dial Base Dia: 44mm
Height: 20.5mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Double Winged Knob

DWK-20 Double Winged Knob



Base Dia: 20mm
Height: 16.6mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Single Winged Knob

SK-20 22.5mm Single Winged knob with Line & Cap Line on Cap (Optional)



Knob Dia: 20mm
Wing Dia: 22.5mm
Height: 16mm
Shaft Dia: 6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Round Knob with Marked Dial

SK-50 38mm Round knob with 50mm marked Dial & Cap



Knob Dia: 38mm
Dial Base Dia: 50mm
Height: 22mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Knob with Lined Cap

SK-19 19mm Knob with Lined Cap



Base Dia: 19.5mm
Height: 16mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Screw fixing
Available in all Standard Colours

Collet Knob with Marked Dial

SK-24 47mm Collet Knob with arrow marked Panel protected Dial & point marked cap



Knob Dia: 25mm
Dial Dia: 47mm
Height: 22.8mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Point Marked Round Knob

SC-15 15mm Lined Knob with point marked on Cap



Base Dia: 15mm
Height: 19mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Insulated Terminals

Round Collet Knob

SC-20 19.5mm Designed Collet Knob with self embossed line & Cap



Base Dia: 19.5mm
Height: 15.6mm
Shaft Dia: 6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Round Collet Knob

CK-10 20mm Round Knob with Lined Cap



Base Dia: 20mm
Height: 16.4mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Winged Collet Knob

CK-15 Four Winged knob with Line marked Cap
Choice of colour combination for Body & Cap



Base Dia: 22.8mm
Height: 20.6mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet type
Available in all Standard Colours

Round Knob

CK-24 25mm Round Knob with Marked Cap



Base Dia: 25mm
Height: 17mm
Shaft Dia: 4.1mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Single Winged Knob

CK-25 25mm Single Winged Knob with Line & Cap
Line on Cap (Optional)



Knob Dia: 25mm
Wing Dia: 29.5mm
Height: 16.5mm
Shaft Dia: 5.9mm/6.1mm/6.4mm
Collet Type
Available in all Standard Colours

Miniature Terminal

ST-5 Miniature Terminal insulated captive screw type 5Amps



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 5Amps
Contact Resistance: <8mW
Rated Impulse: 0.5KV for 1min.

Colour Capped Terminal

ST-6 Terminal Insulated Captive screw cap with different colour caps for upto 10Amps applications



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW
Rated Impulse: 1.0KV for 1min.

Colour Capped Terminal

ST-6/S Terminal Insulated with different colour caps 10Amps with extra stud length



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW
Rated Impulse: 1.0KV for 1min.

Colour Capped Terminal

ST-6/B Terminal Insulated Captive screw cap with different colour caps for upto 10Amps applications for thicker panels



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW
Rated Impulse: 1.0KV for 1min.

Terminal 10Amps

ST-10 Terminal Insulated Captive screw cap 10Amps



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW
Rated Impulse: 1.0KV for 1min.

Terminal 10Amps

ST-10/P Terminal 10Amps for Insulated Panels



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW

Terminal Square Based

ST-10/SB Terminal Square Based 10Amps for Insulated Panels (Marking Optional)



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW

Terminal 12Amps

ST-15 Terminal Insulated Captive screw cap 12Amps



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 12Amps
Contact Resistance: <8mW
Rated Impulse: 1.0KV for 1min.

Terminal 10Amps

SAP-10 Terminal 10Amps for Insulated Panels



Insulation: Polyamide
Conductor: Brass plated Nickel / Gold
Available in all Standard Colours

Terminal 10Amps

SS-10 Terminal Insulated Captive screw cap 10Amps



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW
Rated Impulse: 1.0KV for 1min.

Terminal 15Amps

SS-15 Terminal Insulated Captive screw cap for 15Amps applications



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 15Amps
Contact Resistance: <8mW
Rated Impulse: 1.5KV for 1min.

Terminal 15Amps

SS-15/B Insulated Terminal with Captive head to cover 4mm Banana Plug



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 15Amps
Contact Resistance: <8mW
Rated Impulse: 1.5KV for 1min.

Terminal 15Amps

SS-15/P Terminal with Captive head for insulated panels



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 10Amps
Contact Resistance: <8mW

Terminal 15Amps

SS-15/SB Terminal with Captive head & square base for insulated panels



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 15Amps
Contact Resistance: <8mW
Rated Impulse: 1.5KV for 1 min.

Terminal 15Amps

SBT-14 Terminal Insulated Captive screw cap 15Amps



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 15Amps
Contact Resistance: <8mW
Rated Impulse: 1.5KV for 1min.

Round Knob

SBT-15 Terminal Insulated Captive screw cap 15Amps



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 15Amps
Contact Resistance: <8mW
Rated Impulse: 1.5KV for 1min.

Terminal 30Amps

ST-33 Insulated Terminal with Captive head



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 30Amps
Contact Resistance: <8mW
Rated Impulse: 2.5KV for 1min.

Terminal 30Amps

WT-33 Insulated Winged Terminal Captive head with or without 4mm Banana jack



Insulation: Polyamide.
Conductor: Brass
Finish: Nickel / Gold
Rated Current: 30Amps
Contact Resistance: <8mW
Rated Impulse: 2.0KV for 1min.

Shrouded Socket Snap-in-type

SS-6/SD 4mm Shrouded Socket snap-in-type for 2mm thick panel 'D' type



Mtrl: Polyamide. Conductor: Brass
Finish: Gold / Silver/ Tin
Rated Voltage: 1500V
Rated Current: 24Amps
Rated Impulse: 6KV
Contact Resistance: <5mW
Mounting: Snap-in-type





Manufacturers and Exporters of Educational Testing & Measuring Instruments,
Hardware Components and Accessories for Electronic Instrumentation

1-34/43, Sarvodaya Nagar, Near Aaray Signal, Western Express Highway, Goregaon (E), Mumbai. 400063. Maharashtra, INDIA

<p>SC-10-6P</p>  <p>Base Dia: 10mm Height : 15.6mm</p>	<p>PN-3-6P</p>  <p>Base Dia: 9.3mm Height : 12.5mm</p>	<p>PN-43-6P</p>  <p>Base Dia: 11mm Height : 12.0mm</p>	<p>SK-1-6P</p>  <p>Base Dia: 12mm Height : 10.5mm</p>
<p>PN-16-6P</p>  <p>Base Dia: 15.8mm Height : 15.2mm</p>	<p>PN-35-6P</p>  <p>Base Dia: 16.1mm Height : 15.3mm</p>	<p>PN-20-6P</p>  <p>Base Dia: 15.6mm Height : 19.1mm</p>	<p>PN-15-6P</p>  <p>Base Dia: 20.0mm Height : 15.8mm</p>
<p>SK-2-6P</p>  <p>Base Dia: 12mm Height : 8.0mm</p>	<p>PN-38-6P</p>  <p>Base Dia: 13mm Height : 15.0mm</p>	<p>PN-1/N-6P</p>  <p>Base Dia: 15.0mm Height : 15.5mm</p>	<p>SC-15-6P</p>  <p>Base Dia: 15.5mm Height : 18.0mm</p>
<p>PN-8-6P</p>  <p>Base Dia: 18.9mm Height : 18.2mm</p>	<p>PN-23-6P</p>  <p>Base Dia: 21.0mm Height : 16.0mm</p>	<p>PN-22-6P</p>  <p>Base Dia: 22.0mm Height : 21.0mm</p>	<p>PN-25-6P</p>  <p>Base Dia: 24.0mm Height : 15.3mm</p>

